

STANDARD INFORMATION

Standard: UL 2442

Standard ID: Wall and Ceiling Mounts and Accessories [UL 2442:2019 Ed.2+R:20Jul2023]

Previous Standard ID: Wall and Ceiling Mounts and Accessories [UL 2442:2019 Ed.2+R:13Jan2023]

EFFECTIVE DATE OF NEW/REVISED REQUIREMENTS

Effective Date: **July 20, 2025**

IMPACT, OVERVIEW, AND ACTION REQUIRED

Impact Statement: Per our accreditation, Intertek is required to review reports against the standard revisions to confirm compliance. Once compliance is confirmed, the standard reference in the report is updated to show continued compliance to the technical requirements of the standard. Reports not updated to this version by the effective date above will be withdrawn.

Overview of Changes: Modification to flammability requirements. Specific details of new/revised requirements are found in table below.

Current Listings Not Active? – Please immediately identify any current Listing Reports or products that are no longer active and should be removed from our records. We will do this at no charge as long as Intertek is notified in writing prior to the review of your reports.



STANDARD INFORMATION

CLAUSE	VERDICT	COMMENT
		<i>Additions to existing requirements are <u>underlined</u> and deletions are shown lined-out below.</i>
37	Info	Flammability of Mounts A molding, cover, shelf, top cap, or similar part not forming an electrical enclosure, that is formed of polymeric material shall be classed HB or higher in accordance with the Standard for Tests for Flammability of Plastic Materials for Parts in Devices and Appliances, UL 94. Exception: This requirement does not apply to the following: a) External accessories that are not permanently attached to the mount, such as a screwdriver, container of lubricating oil, and similar accessories. b) Small parts that satisfy all of the following: 1) The maximum volume does not exceed 0.122 inch³ (2 cm³), and 2) The maximum dimension does not exceed 1.18 inches (3 cm). c) Polymeric material 0.010 inch (0.254 mm) thick or less. <u>Polymeric or similar material used in the construction of a wall or ceiling mount assembly that is used as an enclosure or support for live parts shall have a minimum flammability classification of HB. The flammability classification is to be determined by tests described in the Standard for Tests for Flammability of Plastic Materials for Parts in Devices and Appliances, UL 94. A material classified using 1/8-inch (3.2 mm) thick bar specimens is able to be employed in thicknesses less than 1/8 inch in the wall or ceiling mount assembly.</u>
37.3		